



SECTION A-A

GENERAL INFORMATION:-

General Information

1. Lens material - Optical PC
 2. Operating Temperature range -40° ~ $+110^{\circ}$ (Upper Limit $+130^{\circ}$)
 3. Storage Temperature range -40° ~ $+110^{\circ}$ (Upper Limit $+130^{\circ}$ C)
- Average transmittance in visible spectrum 400nm-700nm > 90%

Usage and Maintenance:

1. If necessary, clean lenses with mild soap, water and soft cloth.
2. Never use any commercial cleaning solvents like Alcohol.
3. Handel and install lenses with wearing gloves, skin oils may Damage lenses or its optical characteristics.

Open Tolrence $\pm 0.2\text{mm}$

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS			DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
SURFACE FINISH:			OPTIKS KARKHANA INDIA PVT. LTD. Part Name:- 200W Highbay 60° Drawing Number:- OKIPL-0151 Rev.00 Part Number:- OK151-3030-60°		
TOLERANCES:					
LINEAR:					
ANGULAR:					
DRAWN	NAME Pradyumna Shandilya	SIGNATURE	DATE 25/09/2019		
CHK'D	Kapil Kaushik		25/09/2019		
APP'VD	Kapil Kaushik		25/09/2019		
MATERIAL: POLYCARBONATE			Part Number:- OK151-3030-60°		A3