



- LENS
- HOLDER
- LED

GENERAL INFORMATION

1. Lens material-Optical PC
 2. Operating Temperature rang; (40 to+100)deg.Upper limit ; +130 deg
 - 3.Storage tempereture range; (40 to+100)deg.Upper limit;+130 deg.
- Average transmittance in visible spectrum 400nm-700nm>90%
- Usage and Maintenance

- 1.If necessary ,clean lenses with mild soap,water and soft cloth.
- 2.Never use any commercial cleaning solvents like alcohol.
- 3.Handel and install lenses with wearing gloves.
- 4.skin oils may damage lenses or its optical characteristics

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 9001:2015 Class M3 and applies if not otherwise shown in the drawing.

ALL DIMENSIONS ARE IN MM
COMMON TOLERANCE :- \pm 0.15

	DEBURE & BREAK SHARP EGGES	DO NOT SALE DRAWING	REVISION		REMARK.
	NAME	SIGNATURE	DATE	OPTIKS MECHATRONICS INDIA PVT.LTD	
DRAWN	A. PATI		03-07-2020	PART NAME	SINGEL LENS 3°-3535-LED & HOLDER
CHECKED	SHASHANK .D		03-07-2020	DRAWING NUMBER	OMPL -234- REV 00
APPROVED	Pradyumna shandilya		03-07-2020	PART NUMBER	OM234-1X1-3535-3°
MATERIAL	POLYCARBONATE		SCALE :	2:1	
WEIGHT			FIRST ANGLE PROJECTION		

This Drawing Is a Property Of Optiks Mechatronics Pvt.Ltd. It May Not Be Copied Or Otherwise Distributed Without Written Permission