



ALL DIMENSIONS ARE IN MM  
COMMON TOLERANCE :-  $\pm 0.15$

**GENERAL INFORMATION**

1. Lens material-Optical PC
  2. Operating Temperature rang; (40 to+100)deg.Upper limit ; +130 deg
  3. Storage tempereture range; (40 to+100)deg.Upper limit;+130 deg.
- Average transmittance in visible spectrum 400nm-700nm>90%
- Usage and Maintenance
- 1.If necessary ,clean lenses with mild soap,water and soft cloth.
  - 2.Never use any commercial cleaning solvents like alcohol.
  - 3.Handel and install lenses with wearing gloves.
  - 4.skin oils may damage lenses or its optical characteristics

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 9001:2015 Class M3 and applies if not otherwise shown in the drawing.

		DEBURE & BREAK SHARP EGGES	DO NOT SCALE DRAWING		REVISION	REMARK.
	NAME	SIGNATURE	DATE	OPTIKS MECHATRONICS INDIA PVT.LTD		
DRAWN	SOMANATH		23-10-2021	PART NAME	1X1 SINGLE FOCUS LENS 25°	
CHECKED	SOMANATH		23-10-2021	DRAWING NUMBER	OMPL-399_REV-00	
APPROVED	Pradyumna shandilya		23-10-2021	PART NUMBER	OMPL-399_1X1-25°	
MATERIAL		POLYCARBONATE		SCALE :	5:1	
WEIGHT		2.1 gm		FIRST ANGLE PROJECTION		
						This Drawing Is a Property Of Optiks Mechatronics Pvt.Ltd. It May Not Be Copied Or Otherwise Distributed Without Written Permission